

TMP-22X

(R24-1001)

Touch Monitor



Product Overview

The TMP-22X is a 21.5-inch touch monitor display designed to enhance your interactive solutions. It features an accurate multi touch panel, that provides high brightness and received a non-glare treatment for enhanced visibility. The TMP-22X is easily installable with its VESA mounting frame, ensuring setup is a breeze. This makes the TMP-22X the perfect touchscreen monitor for a range of solutions from point of sale, self-service, and interactive signage to wayfinding, queuing and customer feedback.



The 10-point PCAP touch panel enhances the TMP-22X by providing precise multi-touch capabilities, improving user interaction, responsiveness, and enabling an intuitive experience.



The TMP-22X comes with a new non-glare coating, contributing to a more comfortable viewing experience by reducing reflections, enhancing visibility and diminishing eye strain.



Designed to operate 24/7, the TMP-22X ensures business continuity by only making use of high-quality components.



The TMP-22X ensures your solution can keep running without interference, and is backed up by a 3-year warranty.




Enjoy a simplified installation process. The TMP-22X is easy to install with its VESA mounting frame. You will be up and running in no-time.

TMP-22X (R24-1001)

Article code: 3022105


Technical Drawing



Sustainability

At ProDVX we are committed to doing our part when it comes to the environment. Our products are designed to have the lowest possible impact on the environment, from inception to product retirement. We also strive to operate our offices and warehouse in a carbon-neutral manner. Our aim is to lead the way in conducting responsible business in the digital signage hardware industry.

I/O Overview



Optional Accessories

Please contact your account manager for accessories

* Compatible with all ProDVX VESA 75 stands, mounts & brackets.

TMP-22X (R24-1001)

Article code: 3022105

Product Specifications

Certification:

CE,RoHS,REACH

Panel

LCD	1920x1080xRGB@60Hz
Type	TFT LCD IPS
Size	21.5
Contrast	3000 to 1
Viewing Angle	H178 / V178
Colours	8 bit LVDS (16.7M) 72%NTSC CIE1931
Response time	18 ms
Backlight	Edge-LED backlight
BLU	250 cd/m2
Cover glass	>6H - 2.05mm
Treatment	Non-glare
Haze	4~10%
Touch type	10 TP Pcap 20ms

Special

PoE	N.A.
IEEE 802.1x	N.A.
Cooling	Fanless
HDMI-in	HDMI
HDMI-out	N.A.
WiFi	N.A.
Bluetooth	N.A.
LAN	N.A.
Audio internal	2 x 2 W
Audio external	N.A.
Microphone	N.A.
USB ports	1x USB 2.0 type A
OTG	N.A.
Other ports	N.A.
PoGo slots	N.A.
NFC	N.A.
Camera	N.A.
Barcode scan	N.A.
LED	N.A.
Operating hrs	24h / 7d
MTBF	45,000 hours demonstrated
Clock batt.	N.A.
Alternative OS	N.A.
Power input	12 V / 2 A (EU, UK, US)
Operating temp	0 ~ 40 degrees C
Storage temp	-10~55 degrees C
Humidity	0 ~ 95% non-condensing
Warranty	3 years
Orientation	Landscape,Portrait,Table Mode
SIM card slot	N.A.
Power usage	10 Watt
OSD language	no OSD

Frame

Size	387,3 x 241,2 x 27,2 mm
Weight	1200 g
Material	ABS+PC (Macrolon)
VESA	VESA 100
Color	Black